

67840 U.S. PTO
6708/841847
05/05/97

CONTINUATION PROGRAM APPLICATION TRANSMITTAL FORM

ANTICIPATED CLASSIFICATION OF THIS APPLICATION

Class: 424 Subclass:

PRIOR APPLICATION

Examiner: M. Cebulak

Art Unit: 1209

To the Assistant Commissioner for Patents:

This is a Request for filing a continuation application under 37 CFR 1.60, of pending prior Application No. 08/405,447, filed on March 16, 1995, which is a continuation of U.S. Patent Application No. 08/099,951, filed on July 30, 1993, of Ernest G. Schutt, et al. for STABILIZED MICROBUBBLE COMPOSITIONS.

- (X) Enclosed is a copy of the latest inventor-signed prior application, including the drawings and the oath or declaration as originally filed. I hereby verify that the attached papers are a true copy of the latest inventor-signed prior Application No. 08/405/447 as originally filed on March 16, 1995, which is a file-wrapper continuation of U.S. Patent Application No. 08/099,951 filed on July 30, 1993, and further that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

- (X) The filing fee is calculated below:

FOR	NUMBER FILED	NUMBER EXTRA	RATE	FEE
Basic Fee			\$385	\$385
Total Claims	1 - 20 =	0 x	\$11	\$0
Independent Claims	1 - 3 =	0 x	\$40	\$0
If application contains any multiple dependent claims(s), then add			\$130	\$)
			TOTAL FILING FEE	\$385

- (X) The Commissioner is hereby authorized to charge any fees which may be required, or credit any overpayment to Deposit Account No. 11-1410. A duplicate copy of this sheet is enclosed.
- (X) A check in the amount of \$385 is enclosed.
- (X) Cancel in this application original Claims 2-61 of the prior application before calculating the filing fee.

-
- (X) Amend the title to read -- STABLE, GAS-FILLED MICROBUBBLE DISPERSIONS --
- (X) Amend the specification by replacing the first sentence with the following: "This application is a continuation of U.S. Patent Application No. 08/405,447, filed March 16, 1995, which is a continuation of U.S. Patent Application No. 08/099,951, filed July 30, 1993.
- (X) The prior application is assigned of record to Alliance Pharmaceutical Corp.
- (X) A verified statement claiming small entity status is enclosed.
- (X) A copy of the verified statement claiming small entity status filed in the prior application is enclosed.
- (X) An Associate Power of Attorney.
- (X) An Information Disclosure Statement.
- (X) PTO Form 1449 listing one hundred seventeen (117) references.
- (X) Return prepaid postcard.
- (X) The power of attorney in the prior application is to the law firm of Knobbe, Martens, Olson & Bear, LLP.
- (X) The power appears in the original papers in the prior application.
- () Since the power does not appear in the original papers, a copy of the power in the prior application is enclosed.

Address all future communications to:

Ned A. Israelsen
Knobbe, Martens, Olson & Bear, LLP
620 Newport Center Drive
Sixteenth Floor
Newport Beach, CA 92660

Date: May 5, 1997

Signature: _____


Ned A. Israelsen
Registration No. 29,655
Attorney of Record

INTELLECTUAL PROPERTY LAW

KNOBBE, MARTENS, OLSON & BEAR

A LIMITED LIABILITY PARTNERSHIP INCLUDING
PROFESSIONAL CORPORATIONS

LOUIS J. KNOBBE*
 DON W. MARTENS*
 GORDON H. OLSON**
 JAMES B. BEAR
 DARRELL L. OLSON*
 WILLIAM B. BUNKER
 NED A. ISRAELSEN
 DREW S. HAMILTON
 WILLIAM H. NIEMAN
 LOWELL ANDERSON
 ARTHUR S. ROSET
 JAMES F. LESNIAK
 JERRY T. SEWELL
 JOHN B. SGANGA, JR.
 EDWARD A. SCHLATTER
 GERARD VON HOFFMANN
 JOSEPH R. RE
 CATHERINE J. HOLLAND
 JOHN M. CARSON
 KAREN VOGEL WEIL*
 ANDREW H. SIMPSON
 JEFFREY L. VAN HOOSER
 DANIEL E. ALTMAN
 ANITA M. KIRKPATRICK

ERNEST A. BEUTLER
 MARGUERITE L. GUNN
 STEPHEN C. JENSEN
 VITO A. CANUSO III
 WILLIAM H. SHREVE
 LYNDIA J. ZADRA-SYMEST††
 STEVEN J. NATAPUSKY
 PAUL A. STEWART
 JOSEPH F. JENNINGS
 CRAIG S. SUMMERS
 ANNEMARIE KAISER
 BRENTON R. BABCOCK†
 MICHAEL H. TRENHOLM
 DIANE M. REED
 NANCY WAYS VENSKO
 JONATHAN A. BARNEY
 RONALD J. SCHOENBAUM
 RICHARD C. GILMORE
 JOHN R. KING
 WILLIAM S. REIJUS
 CHRISTINE A. GRITZMACHER
 JOHN P. GIEZENTANNER
 ADEEL S. AKHTAR
 FREDERICK S. BERRETTA

PATENT, TRADEMARK AND COPYRIGHT CAUSES

KOLL CENTER SAN DIEGO
 501 WEST BROADWAY
 SUITE 1400
 SAN DIEGO, CALIFORNIA 92101-3505
 (619) 235-8550
 FAX (619) 235-0176
 INTERNET: WWW.KMOB.COM

THOMAS R. ARNO
 DAVID N. WEISS
 CHRISTOPHER A. COLVIN
 DANIEL HART
 JAMES T. HAGLER
 DOUGLAS G. MUEHLHAUSER
 LORI L. YAMATO
 MOSES MARES
 STEPHEN M. LOBBIN
 RICHARD KIM
 ANN A. BYUN
 GLENN R. SMITH
 ROBERT F. GAZDZINSKI
 FRED C. HERNANDEZ
 STACEY R. HALPERN†
 R. SCOTT WEIDE
 MICHAEL K. FRIEDLAND
 DALE C. HUNT
 CHAD W. MILLER
 JOHN C. WILSON
 LEE W. HENDERSON
 LENA A. BASILE
 DEBORAH S. SHEPHERD

OF COUNSEL
 JERRY R. SEILER
 JAPANESE PATENT ATTYS
 YASUO MURAMATSU†††
 KATSUHIRO ARAI
 SCIENTISTS & ENGINEERS
 (NON-LAWYERS)
 RAIMOND J. SALENIKS**
 RENEER E. CANUSO**
 MICHAEL L. FULLER**
 NEIL S. BARTFELD**
 MICHAEL J. GILLY
 HALIT N. YAKUPOGLU
 STANLEY W. HUTH
 DANIEL E. JOHNSON**
 JIAWEI HUANG

Assistant Commissioner for Patents
 Washington, D.C. 20231

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

Attorney Docket No. : ALLIA.62F1C3
Applicant(s) : Ernest G. Schutt, et al.
For : STABLE, GAS-FILLED MICROBUBBLE DISPERSIONS
Attorney : Ned A. Israelsen
"Express Mail"
Mailing Label No. : TB82330181XUS
Date of Deposit : May 5, 1997

I hereby certify that the accompanying

Transmittal in Duplicate; COPY of Specification in 50 pages with unsigned Declaration in 3 pages; COPY of signed Declaration in 3 pages; COPY of 2 Assignments, one in 3 pages, the other in 1 page; COPY Power of Attorney by Assignee in 2 pages; COPY Small Entity Statement(s); Associate Power of Attorney; Information Disclosure Statement; PTO Form 1449 with 0 reference; Check(s) for Filing Fee(s); Return Prepaid Postcard

are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and are addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

John Riedel

NAI-1643:cd
 050597

620 NEWPORT CENTER DRIVE
 SIXTEENTH FLOOR
 NEWPORT BEACH, CALIFORNIA 92660-8016
 (714) 760-0404
 FAX (714) 760-9502

3801 UNIVERSITY AVENUE
 SUITE 710
 RIVERSIDE, CALIFORNIA 92501
 (909) 781-9231
 FAX (909) 781-4507

* A PROFESSIONAL CORPORATION
 † ALSO MEMBER OF D.C. BAR
 †† ALSO BARRISTER AT LAW (U.K.)
 ††† ALSO MEMBER OF CA BAR
 ** U.S. PATENT AGENT

STABILIZED MICROBUBBLE COMPOSITIONS

BACKGROUND OF THE INVENTION1. Field of the Invention

5 The present invention includes a method for preparing stable long-lived microbubbles for ultrasound contrast enhancement and other uses, and to compositions of the bubbles so prepared.

2. Background of the Art

10 Ultrasound technology provides an important and more economical alternative to imaging techniques which use ionizing radiation. While numerous conventional imaging technologies are available, e.g., magnetic resonance imaging (MRI), computerized tomography (CT), and positron emission 15 tomography (PET), each of these techniques use extremely expensive equipment. Moreover, CT and PET utilize ionizing radiation. Unlike these techniques, ultrasound imaging equipment is relatively inexpensive. Moreover, ultrasound imaging does not use ionizing radiation.

20 Ultrasound imaging makes use of differences in tissue density and composition that affect the reflection of sound waves by those tissues. Images are especially sharp where there are distinct variations in tissue density or compressibility, such as at tissue interfaces. Interfaces 25 between solid tissues, the skeletal system, and various organs and/or tumors are readily imaged with ultrasound.

30 Accordingly, in many imaging applications ultrasound performs suitably without use of contrast enhancement agents; however, for other applications, such as visualization of flowing blood in tissues, there have been ongoing efforts to develop such agents to provide contrast enhancement. One particularly significant application for such contrast agents is in the area of vascular imaging. Such ultrasound contrast agents could improve imaging of flowing blood in the heart, 35 kidneys, lungs, and other tissues. This, in turn, would facilitate research, diagnosis, surgery, and therapy related

to the imaged tissues. A blood pool contrast agent would also allow imaging on the basis of blood content (e.g., tumors and inflamed tissues) and would aid in the visualization of the placenta and fetus by enhancing only the
5 maternal circulation.

A variety of ultrasound contrast enhancement agents have been proposed. The most successful agents have generally consisted of microbubbles that can be injected intravenously. In their simplest embodiment, microbubbles are miniature bubbles containing a gas, such as air, and are formed through the use of foaming agents, surfactants, or encapsulating agents. The microbubbles then provide a physical object in the flowing blood that is of a different density and a much higher compressibility than the surrounding fluid tissue and
10 blood. As a result, these microbubbles can easily be imaged with ultrasound.
15

Most microbubble compositions have failed, however, to provide contrast enhancement that lasts even a few seconds, let alone minutes, of contrast enhancement. This greatly limits their usefulness. Microbubbles have therefore been "constructed" in various manners in an attempt to increase their effective contrast enhancement life. Various avenues have been pursued: use of different surfactants or foaming agents; use of gelatins or albumin microspheres that are initially formed in liquid suspension, and which entrap gas during solidification; and liposome formation. Each of these attempts, in theory, should act to create stronger bubble structures. However, the entrapped gases (typically air, CO₂, and the like) are under increased pressure in the bubble
20 due to the surface tension of the surrounding surfactant, as
25 described by the La Place equation ($\Delta P=2\gamma/r$).
30

This increased pressure, in turn, results in rapid shrinkage and disappearance of the bubble as the gas moves from a high pressure area (in the bubble) to a lower pressure environment (in either the surrounding liquid which is not
35

saturated with gas at this elevated pressure, or into a larger diameter, lower pressure bubble).

Solid phase shells that encapsulate gases have generally proven too fragile or to permeable to the gas to have satisfactory *in vivo* life. Furthermore, thick shells (e.g., albumin, sugar, or other viscous materials) reduce the compressibility of the bubbles, thereby reducing their echogenicity during the short time they can exist. Solid particles or liquid emulsion droplets that evolve gas or boil when injected pose the danger of supersaturating the blood with the gas or vapor. This will lead to a small number of large embolizing bubbles forming at the few available nucleation sites rather than the intended large number of small bubbles.

One proposal for dealing with such problems is outlined in Quay, PCT/US92/07250. Quay forms bubbles using gases selected on the basis of being a gas at body temperature (below 37°C), and having reduced water solubility, higher density, and reduced gas diffusivity in solution in comparison to air. Although reduced water solubility and diffusivity can affect the rate at which the gas leaves the bubble, numerous problems remain with the Quay bubbles. Forming bubbles of sufficiently small diameter (e.g., 0.2 μm) requires high energy input. This is a disadvantage in that sophisticated bubble preparation systems must be provided at the site of use. Moreover, The Quay gas selection criteria are incorrect in that they fail to consider certain major causes of bubble shrinkage, namely, the effects of bubble surface tension, surfactants and gas osmotic effects, and these errors result in the inclusion of certain unsuitable gases and the exclusion of certain optimally suitable gases.

Accordingly, a need exists in the art for compositions, and a method to prepare such compositions, that provide, or utilize, a longer life contrast enhancement agent that is

biocompatible, easily prepared, and provides superior contrast enhancement in ultrasound imaging.

Summary of the Invention

- 5 In accordance with the present invention, there is provided an ultrasound contrast enhancement agent that has a prolonged longevity *in vivo*, which consists of virtually any conventional microbubble formulation in conjunction with an entrapped gas or gas mixture that is selected based upon
10 consideration of partial pressures of gases both inside and outside of the bubble, and on the resulting differences in gas osmotic pressure that oppose bubble shrinkage. Gases having a low vapor pressure and limited solubility in blood or serum (i.e., relatively hydrophobic) may advantageously be
15 provided in combination with another gas that is more rapidly exchanged with gases present in normal blood or serum. Surfactant families allowing the use of higher molecular weight gas osmotic agents, and improved methods of bubble production are also disclosed.
- 20 One aspect of the present invention is a stabilized gas filled microbubble preparation, comprising a mixture of a first gas or gases and a second gas or gases within generally spherical membranes to form microbubbles, wherein the first gas and the second gas are respectively present in a molar ratio of about 1:100 to about 1000:1, and wherein the first gas has a vapor pressure of at least about $(760 - x)$ mm Hg at 37°C, where x is the vapor pressure of the second gas at 37°C, and wherein the vapor pressure of each of the first and second gases is greater than about 75 mm Hg at 37°C, with the proviso that the first gas and the second gas are not water vapor. In one embodiment, the second gas comprises a fluorocarbon and the first gas is a nonfluorocarbon, such as nitrogen, oxygen, carbon dioxide, or a mixture thereof.
25
30
35 The microbubbles may advantageously be provided in a liquid medium, such as an aqueous medium, wherein they have

1

a first average diameter, the ratio of the first gas to the
second gas in the microbubbles is at least 1:1, and the
microbubbles are adapted to shrink in the medium as a result
5 of loss of the first gas through the membrane to a second
average diameter of less than about 75% of the first diameter
and then remain stabilized at or about the second diameter
for at least about 1 minute as a result of a gas osmotic
pressure differential across the membrane. Advantageously,
10 the medium is in a container and the microbubbles have
actually been formed in the container. Alternatively, the
medium is blood *in vivo*. In one embodiment, the liquid medium
contains gas or gases dissolved therein with a gas tension of
at least about 700 mm Hg, wherein the first diameter is at
least about 5 μm , and wherein the tension of the gas or gases
15 dissolved in the medium is less than the partial pressure of
the same gas or gases inside the microbubbles.

In a particularly preferred embodiment, the bubble
initially contains at least three gases: a first gas having
a partial pressure far greater than the gas tension of the
20 same gas in the surrounding liquid (e.g., 1.5, 2, 4, 5, 10,
20, 50, or 100 or more times greater than in the surrounding
liquid); a second gas that is retained in the bubble due to
a relatively low permeability of the bubble membrane to the
gas, or a relatively low solubility of the gas in the
25 surrounding medium (as described elsewhere herein), and a
third gas to which the membrane is relatively permeable that
is also present in the surrounding medium. For example, in
an aqueous system exposed to or at least partially
equilibrated with air (such as blood), the first gas may
30 advantageously be carbon dioxide or another gas not present
in large quantities in air or blood; the second gas may be a
fluorocarbon gas, such as perfluorohexane; and the third gas
may be air or a major component of air such as nitrogen or
oxygen.

3

Preferably, the first diameter prior to shrinkage is at least about 10 μm and the second diameter at which the diameter is stabilized is between about 1 μm and 6 μm .

For all of the microbubble preparations or methods described herein, in one preferred embodiment, the second gas has an average molecular weight at least about 4 times that of the first gas. In another preferred embodiment, the second gas has a vapor pressure less than about 750 or 760 mm Hg at 37°C. Moreover, it is preferred that the molar ratio of the first gas to the second gas is from about 1:10 to about 500:1, 200:1, or 100:1. In other preferred embodiments, the second gas comprises a fluorocarbon or a mixture of at least two or three fluorocarbons, and the first gas is a nonfluorocarbon. In some advantageous preparations, the second gas comprises one or more perfluorocarbons. In others, both the first gas and the second gas comprise fluorocarbons. In still others, the microbubbles contain as the first gas, or as the second gas, or respectively as the first and second gases, gaseous perfluorobutane and perfluorohexane in a ratio from about 1:10 to about 10:1. Alternatively, the microbubbles contain as the first gas, or as the second gas, or respectively as the first and second gases, gaseous perfluorobutane and perfluoropentane in a ratio from about 1:10 to about 10:1. It is advantageous that the second gas leave the microbubble much more slowly than does the first gas; thus, it is preferred that the second gas has a water solubility of not more than about 0.5 mM at 25°C and one atmosphere, and the first gas has a water solubility at least about 10 times, and preferably at least 20, 50, 100, or 200 times greater than that of the second gas. Similarly, it is preferred that the permeability of the membrane to the first gas is at least about 5 times, preferably 10, 20, 50, or 100 times greater than the permeability of the membrane to the second gas.

The microbubble preparation may advantageously be contained in a container, having a liquid in the container in admixture with the microbubbles, wherein the container further comprises means for transmission of sufficient ultrasonic energy to the liquid to permit formation of the microbubbles by sonication. In this way, the microbubbles can be formed by the physician (or other professional) immediately before use by applying ultrasonic energy from an outside source to the sterile preparation inside the container. This means for transmission can, for example, be a flexible polymer material having a thickness less than about 0.5 mm (which permits ready transmission of ultrasonic energy without overheating the membrane). Such membranes can be prepared from such polymers as natural or synthetic rubber or other elastomer, polytetrafluoroethylene, polyethylene terephthalate, and the like.

In the microbubble preparations of the invention, the membrane enclosing the gas is preferably a surfactant. One preferred type of surfactant comprises a non-Newtonian viscoelastic surfactant, alone or in combination with another surfactant. Other preferred general and specific categories of surfactants include carbohydrates, such as polysaccharides, derivatized carbohydrates, such as fatty acid esters of sugars such as sucrose (preferably sucrose stearate), and proteinaceous surfactants including albumin. Alternatively, the membrane of the microbubble need not be a fluid (such as a surfactant), but instead can be a solid or semi-solid, such as hardened, thickened, or denatured proteinaceous material (e.g. albumin), carbohydrates, and the like.

One advantageous form of the invention is a kit for use in preparing microbubbles, preferably at the site of use. This kit may comprise sealed container (such as a vial with a septum seal for easy removal of the microbubbles using a hypodermic syringe), a liquid in the container (such as water or a buffered, isotonic, sterile aqueous medium), a

surfactant in the container, and a fluorocarbon gas (including a fluorocarbon vapor) in the container, wherein the liquid, the surfactant, and the fluorocarbon gas or vapor are together adapted to form microbubbles upon the application of energy thereto. The energy advantageously may be simple shaking energy, either manual or mechanical, stirring or whipping, or ultrasonic energy. The kit preferably includes means in the container for permitting transmission of sufficient external ultrasonic energy to the liquid to form microbubbles in the container. As above, the means for transmission can in one embodiment comprise a flexible polymer membrane having a thickness less than about 0.5 mm. In one embodiment, the kit further includes a nonfluorocarbon gas in the container, wherein the molar ratio of the nonfluorocarbon gas to the fluorocarbon gas is from about 1:10 to about 1000:1, with the proviso that the nonfluorocarbon gas is not water vapor. In all of the kits of the present invention, the surfactant, the gas or gases, and the other elements of the kit may in some embodiments be the same as recited above for the microbubble preparation per se.

In another embodiment, the kit comprises a container, dried liquid-soluble void-containing structures in the container, the void-containing structures defining a plurality of voids having an average diameter less than about 100 μm , a gas in the voids, and a surfactant, wherein the void-containing structures, the gas, and the surfactant are together adapted to form microbubbles upon addition to the container of a liquid in which the void-containing structures are soluble. These void-containing structures can be made at least in part of the surfactant, e.g., by lyophilization of void-forming material or by spray drying, or can be formed from any other liquid soluble (preferably water soluble) film-forming material, such as albumin, enzymes, or other proteins, simple or complex carbohydrates or polysaccharides, and the like. The surfactants used in the kit can

5

advantageously be those described above in connection with the microbubble preparations per se.

The present invention also includes a method for forming microbubbles, comprising the steps of providing a first gas, a second gas, a membrane forming material, and a liquid, wherein the first gas and the second gas are present in a molar ratio of from about 1:100 to about 1,000:1, and wherein the first gas has a vapor pressure of at least about (760 - x) mm Hg at 37°C, where x is the vapor pressure of the second 10 gas at 37°C, and wherein the vapor pressure of each of the first and second gases is greater than about 75 mm Hg at 37°C, with the proviso that the first gas and the second gas are not water vapor, and surrounding the first and second gases with the membrane forming material to form microbubbles 15 in the liquid. The membrane forming materials and gases may be as described above. The method preferably further comprises the steps of initially forming microbubbles having a first average diameter wherein the initial ratio of the first gas to the second gas in the microbubbles is at least about 1:1, contacting the microbubbles having a first average diameter with a liquid medium, shrinking the microbubbles in the medium as a result of loss of the first gas through the membrane, and then stabilizing the microbubbles at a second average diameter of less than about 75% of the first diameter 20 for a period of at least one minute. Preferably, the microbubbles are stabilized at the second diameter by providing a gas osmotic pressure differential across the membrane such that the tension of a gas or gases dissolved in the medium is greater than or equal to the pressure of the same gas or gases inside the microbubbles. In one embodiment, the first diameter is at least about 5 μm . 25 30 35

The invention also includes a method for forming microbubbles, comprising the steps of providing dried liquid-soluble void-containing structures, the void-containing structures defining a plurality of voids having a diameter

less than about 100 μm , providing a gas in the voids, providing a surfactant, combining together the void-containing structures, the gas, the surfactant, and a liquid in which the void-containing structures are soluble, and dissolving the void-containing structures in the liquid whereby the gas in the enclosures forms microbubbles that are surrounded by the surfactant. As with the kit, preferred void-containing structures are formed of protein, surfactant, carbohydrate, or any of the other materials described above.

Finally, the present invention includes a method for imaging an object or body, comprising the steps of introducing into the object or body any of the aforementioned microbubble preparations and then ultrasonically imaging at least a portion of the object or body. Preferably, the body is a vertebrate and the preparation is introduced into the vasculature of the vertebrate. The method may further include preparing the microbubbles in any of the aforementioned manners prior to introduction into the animal.

Detailed Description of the Invention

As used in the present description and claims, the terms "vapor" and "gas" are used interchangeably. Similarly, when referring to the tension of dissolved gas in a liquid, the more familiar term "pressure" may be used interchangeably with "tension." "Gas osmotic pressure" is more fully defined below, but in a simple approximation can be thought of as the difference between the partial pressure of a gas inside a microbubble and the pressure or tension of that gas (either in a gas phase or dissolved in a liquid phase) outside of the microbubble, when the microbubble membrane is permeable to the gas. More precisely, it relates to differences in gas diffusion rates across a membrane. The term "membrane" is used to refer to the material surrounding or defining a microbubble, whether it be a surfactant, another film forming liquid, or a film forming solid or semisolid. "Microbubbles" are considered to be bubbles having a diameter between about

0.5 and 300 μm , preferably having a diameter no more than about 200, 100, or 50 μm , and for intravascular use, preferably not more than about 10, 8, 7, 6, or 5 μm (measured as average number weighted diameter of the microbubble composition). When referring to a "gas," it will be understood that mixtures of gases together having the requisite property fall within the definition, except where the context otherwise requires. Thus, air may typically be considered a "gas" herein.

The present invention provides microbubbles that have a prolonged longevity *in vivo* that are suitable for use as ultrasound contrast enhancement agents. Typical ultrasound contrast enhancement agents exhibit contrast enhancement potential for only about one pass through the arterial system, or a few seconds to about a minute, and thus do not survive past the aorta in a patient following intravenous injection. In comparison, contrast agents prepared in accordance with the present invention continue to demonstrate contrast enhancements lives measured in multiple passes through the entire circulatory system of a patient following intravenous injection. Bubble lives of several minutes are easily demonstrated. Such lengthening of contrast enhancement potential during ultrasound is highly advantageous. In addition, the contrast enhancement agents of the invention provide superior imaging; for example, clear, vivid, and distinct images of blood flowing through the heart, lungs, and kidneys are achieved. Thus small, nontoxic doses can be administered in a peripheral vein and used to enhance images of the entire body.

While bubbles have been shown to be the most efficient ultrasound scatterers for use in intravenous ultrasound contrast agents, their main practical drawback is the extremely short lifetime of the small (typically less than 5 microns diameter) bubbles required to pass through capillaries in suspension. This short lifetime is caused by

the increased gas pressure inside the bubble, which results from the surface tension forces acting on the bubble. This elevated internal pressure increases as the diameter of the bubble is reduced. The increased internal gas pressure
5 forces the gas inside the bubble to dissolve, resulting in bubble collapse as the gas is forced into solution. The LaPlace equation, $\Delta P = 2\gamma/r$, (where ΔP is the increased gas pressure inside the bubble, γ is the surface tension of the bubble film, and r is the radius of the bubble) describes the
10 pressure exerted on a gas bubble by the surrounding bubble surface or film. The La Place pressure is inversely proportional to the bubble radius; thus, as the bubble shrinks, the La Place pressure increases, increasing the rate of diffusion of gas out of the bubble and the rate of bubble
15 shrinkage.

It was surprisingly discovered that gases and gas vapor mixtures which can exert a gas osmotic pressure opposing the LaPlace pressure can greatly retard the collapse of these small diameter bubbles. In general, the invention uses a primary modifier gas or mixture of gases that dilute a gas osmotic agent to a partial pressure less than the gas osmotic agent's vapor pressure until the modifier gas will exchange with gases normally present in the external medium. The gas osmotic agent or agents are generally relatively hydrophobic
20 and relatively bubble membrane impermeable and also further possess the ability to develop gas osmotic pressures greater than 75 or 100 Torr at a relatively low vapor pressure.
25

The process of the invention is related to the well known osmotic effect observed in a dialysis bag containing a solute that is substantially membrane impermeable (e.g. PEG, albumin, polysaccharide, starch) dissolved in an aqueous solution is exposed to a pure water external phase. The solute inside the bag dilutes the water inside the bag and thus reduces the rate of water diffusion out of the bag relative to the rate of pure water (full concentration) diffusion into the bag. The bag will expand in volume until
30
35

an equilibrium is established with an elevated internal pressure within the bag which increases the outward diffusional flux rate of water to balance the inward flux rate of the pure water. This pressure difference is the
5 osmotic pressure between the solutions.

In the above system, the internal pressure will slowly drop as the solute slowly diffuses out of the bag, thus reducing the internal solute concentration. Other materials dissolved in the solution surrounding the bag will reduce
10 this pressure further, and, if they are more effective or at a higher concentration, will shrink the bag.

It was observed that bubbles of air saturated with selected perfluorocarbons grow rather than shrink when exposed to air dissolved in a liquid due to the gas osmotic
15 pressure exerted by the perfluorocarbon vapor. The perfluorocarbon vapor is relatively impermeable to the bubble film and thus remains inside the bubble. The air inside the bubble is diluted by the perfluorocarbon, which acts to slow the air diffusion flux out of the bubble. This gas osmotic
20 pressure is proportional to the concentration gradient of the perfluorocarbon vapor across the bubble film, the concentration of air surrounding the bubble, and the ratio of the bubble film permeability to air and to perfluorocarbon.

As discussed above, the LaPlace pressure is inversely
25 proportional to the bubble radius; thus, as the bubble shrinks, the LaPlace pressure increases, increasing the rate of diffusion of gas out of the bubble and the rate of bubble shrinkage, and in some cases leading to the condensation and virtual disappearance of a gas in the bubble as the combined
30 LaPlace and external pressures concentrate the osmotic agent until its partial pressure reaches the vapor pressure of liquid osmotic agent.

We have discovered that conventional microbubbles that contain any single gas will subsist in the blood for a length
35 of time that depends primarily on the arterial pressure, the bubble diameter, the membrane permeability of the gas through

the bubble's surface, the mechanical strength of the bubble's surface, the presence, absence, and concentration of the gases that are ordinarily present in the blood or serum, and the surface tension present at the surface of the bubble
5 (which is primarily dependent on the diameter of the bubble and secondarily dependent on the identity and concentration of the surfactants which form the bubble's surface). Each of these parameters are interrelated, and they interact in the bubble to determine the length of time that the bubble will
10 last in the blood.

The present invention includes the discovery that a single gas or a combination of gases can together act to stabilize the structure of the microbubbles entraining or entrapping them. Essentially, the invention utilizes a first
15 gas or gases (a "primary modifier gas") that optionally is ordinarily present in normal blood and serum in combination with one or more additional second gases (a "gas osmotic agent or agents" or a "secondary gas") that act to regulate the osmotic pressure within the bubble. Through regulating
20 the osmotic pressure of the bubble, the gas osmotic agent (defined herein as a single or mixture of chemical entities) exerts pressure within the bubble, aiding in preventing deflation. Optionally, the modifier gas may be a gas that is not ordinarily present in blood or serum. However, the
25 modifier gas must be capable of diluting and maintaining the gas osmotic agent or agents at a partial pressure below the vapor pressure of the gas osmotic agent or agents while the gases in blood or other surrounding liquid diffuse into the bubble. In an aqueous medium, water vapor is not considered
30 to be one of the "gases" in question. Similarly, when microbubbles are in a nonaqueous liquid medium, the vapor of that medium is not considered to be one of the "gases."

We have discovered that by adding a gas osmotic agent that has, for example, a reduced membrane permeability
35 through the bubble's surface or reduced solubility in the external continuous phase liquid phase, the life of a bubble

formed therewith will be radically increased. This stabilizing influence can be understood more readily through a discussion of certain theoretical bubbles. First, we will consider the effects of arterial pressure and surface tension 5 on a hypothetical microbubble containing only air.

Initially, a hypothetical bubble containing only air is prepared. For purposes of discussion, this bubble will initially be considered to have no LaPlace pressure. Generally, when equilibrated at standard temperature and 10 pressure (STP), it will have a internal pressure of 760 Torr of air and the surrounding fluid air concentration will also be equilibrated at 760 Torr (i.e., the fluid has an air tension of 760 Torr). Such a bubble will neither shrink nor grow.

Next, when the above hypothetical bubble is introduced 15 into the arterial system, the partial pressure of air (or air tension) in the blood (the air pressure at which the blood was saturated with air) will also be approximately 760 Torr and there will be an arterial pressure (for the purposes of 20 the this discussion at 100 Torr). This total creates an external pressure on the bubble of 860 Torr, and causing the gases in the bubble to be compressed until the internal pressure increases to 860 Torr. There then arises a difference of 100 Torr between the air pressure inside the 25 bubble and the air tension of the fluid surrounding the bubble. This pressure differential causes air to diffuse out of the bubble, through its air-permeable surface membrane, causing the bubble to shrink (i.e., lose air) as it strives to reach equilibrium. The bubble shrinks until it 30 disappears.

Next, consider the additional, and more realistic, effect on the hypothetical bubble of adding the surface tension of the bubble. The surface tension of the bubble leads to a LaPlace pressure exerted on gas inside the bubble. 35 The total pressure exerted on the gas inside the bubble is computed through adding the sum of the atmospheric pressure,

the arterial pressure and the LaPlace pressure. In a 3 μm bubble a surface tension of 10 dynes per centimeter is attainable with well chosen surfactants. Thus, the LaPlace pressure exerted on the hypothetical 3 μm bubble is approximately 100 Torr and, in addition, the arterial pressure of 100 Torr is also exerted on the bubble. Therefore, in our hypothetical bubble, the total external pressure applied to the gas inside the bubble is 960 Torr.

The bubble will be compressed until the pressure of the air inside the bubble rises to 960 Torr. Accordingly, a concentration differential of 200 Torr arises between the air inside the bubble and the air dissolved in the blood. Therefore, the bubble will rapidly shrink and disappear even more rapidly than it did in the previous case, as it attempts to reach equilibrium.

The discovery of the present invention is illustrated by considering a third hypothetical microbubble containing air and a gas osmotic agent or a secondary gas. Assume that a theoretical bubble, initially having no arterial pressure and no LaPlace pressure, is prepared having a total pressure of 760 Torr, which is made up of air at a partial pressure of 684 Torr and a perfluorocarbon ("PFC") as a gas osmotic agent at a partial pressure of 76 Torr. Further, assume that the perfluorocarbon is selected to have one or more traits that make it capable of acting as an appropriate gas osmotic agent, such as limited bubble membrane permeability or limited solubility in the external liquid phase. There is an initial gas osmotic pressure differential between the 684 Torr of air within the bubble and the 760 Torr of air tension outside the bubble (assuming STP) of 76 Torr. This 76 Torr initial pressure difference is the initial gas osmotic pressure and will cause the bubble to expand. Air from outside of the bubble will diffuse into and inflate the bubble, driven by the osmotic pressure differential, similar to the way water diffuses into a dialysis bag containing a starch solution, and inflates the bag.

The maximum gas osmotic pressure this gas mixture can develop is related to the partial pressure of the PFC and the ratio of the permeability of the PFC to the permeability of the air in the surrounding fluid. In theory, and as observed 5 experimentally, the bubble will grow indefinitely as the system attempts to reach osmotic equilibrium between the concentration of air (equivalent to the partial pressure of air) within the bubble and the concentration of air surrounding the bubble (the air tension).

When the hypothetical mixed gas bubble is exposed to 100 Torr of arterial pressure where the blood has a dissolved air tension of 760 Torr, the total external pressure will equal 860 Torr (760 Torr atmospheric pressure and 100 Torr arterial pressure). The bubble will compress under the arterial 10 pressure, causing the internal pressure of the bubble to reach 860 Torr. The partial pressure of the air will increase to 774 Torr and the partial pressure of the PFC (the second gas) will increase to 86 Torr. The air will diffuse 15 out of the bubble until it reaches osmotic equilibrium with the air dissolved in the blood (i.e., 760 Torr) and the partial pressure of the PFC will increase to 100 Torr. The partial pressure of the PFC will act to counterbalance the 20 pressure exerted due to the arterial pressure, halting shrinkage of the bubble, in each case, assuming that the permeability of the bubble to the PFC is negligible.

When the surface tension or LaPlace pressure component of 100 Torr is added (as discussed above with the air bubble), a total of 200 Torr additional pressure is exerted 25 on the gas in the bubble. Again, the bubble will compress until and the pressure inside the bubble increases to 960 Torr (partial pressure of air 864 and partial pressure of PFC 96). The air will diffuse from the bubble until it reaches 30 760 Torr (in equilibrium with the concentration of air the dissolved in the blood) and the partial pressure of the PFC will increase to 200 Torr, where, again, the gas osmotic pressure induced by the PFC will act to counterbalance the 35

pressure exerted by the LaPlace pressure and the arterial pressure, again, assuming that the membrane permeability of the bubble to the PFC is negligible.

Similarly, if the partial pressure of air in the bubble
5 is lower than the air tension in the surrounding liquid, the bubble will actually grow until the PFC is sufficiently diluted by incoming air so that the pressure of air inside and the air tension outside of the bubble are identical.

Thus, it can be seen has been shown that bubbles can be
10 effectively stabilized through the use of combinations of gases, since the correct combination of gases will result in a gas osmotic pressure differential that can be harnessed to counterbalance the effects of the LaPlace pressure and the arterial pressure exerted on the a gas within the bubble in
15 circulating blood.

Examples of particular uses of the microbubbles of the present invention include perfusion imaging of the venous drainage system of the heart, the myocardial tissue, and determination of perfusion characteristics of the heart and its tissues during stress or exercise tests, or perfusion defects or changes due to myocardial infarction. Similarly, myocardial tissue can be viewed after oral or venous administration of drugs designed to increase the blood flow to a tissue. Also, visualization of changes in myocardial tissue due to or during various interventions, such as coronary tissue vein grafting, coronary angioplasty, or use of thrombolytic agents (TPA or streptokinase) can also be enhanced. As these contrast agents can be administered conveniently via a peripheral vein to enhance the visualization of the entire circulatory system, they will also aid in the diagnosis of Deep Vein Thrombosis and in the ability to ultrasonically monitor the fetus and the umbilical cord.
20
25
30

It should, however, be emphasized that these principles have application beyond ultrasound imaging. Indeed, the present invention is sufficiently broad to encompass the use
35

of gas osmotic pressure to stabilize bubbles for uses in any systems, including nonbiological applications.

In a preferred embodiment, the microbubbles of the present invention have a surfactant-based bubble membrane. 5 However, the principles of the invention can be applied to stabilize microbubbles of virtually any type. Thus, mixed gases or vapors of the type described above can stabilize albumin based bubbles, polysaccharide based microbubbles, spray dried microsphere derived microbubbles, and the like. 10 This result is achieved through the entrapment, within the chosen microbubble, of a combination of gases, preferably a primary modifier gas or mixture of gases that will dilute a gas osmotic agent to a partial pressure less than the gas osmotic agent's vapor pressure until the modifier gas will 15 exchange with gases normally present in the external medium. The gas osmotic agent or agents are generally relatively hydrophobic and relatively bubble membrane impermeable and also further possess the ability to develop gas osmotic pressures greater than 50, 75, or 100 Torr. In one preferred 20 embodiment, the gas vapor pressure of the gas osmotic agent is preferably less than about 760 Torr at 37°C, preferably less than about 750, 740, 730, 720, 710, or 700 Torr, and in some embodiments less than about 650, 600, 500, or 400 Torr.

In preferred embodiments, the vapor pressure of the primary modifier gas is at least 660 Torr at 37°C and the vapor pressure of the gas osmotic agent is at least 100 Torr at 37°C. For *in vivo* imaging mean bubble diameters between 1 and 10 μm are preferred, with 3 to 5 μm most preferred. The invention may in one embodiment also be described as a mixture of a first gas or gases and a second gas or gases within generally spherical membranes to form microbubbles, where the first gas and the second gas are respectively present in a molar ratio of about 1:100, 1:75, 1:50, 1:30, 1:20, or 1:10 to about 1000:1, 500:1, 250:1, 100:1, 75:1 or 35 50:1, and where the first gas has a vapor pressure of at

least about $(760 - x)$ mm Hg at 37°C , where x is the vapor pressure of the second gas at 37°C , and where the vapor pressure of each of the first and second gases is greater than about 75 or 100 mm Hg at 37°C .

5 Microbubbles prepared in accordance with one preferred embodiment of the invention may also possess an additional advantageous property. In one such embodiment, mixtures of nonosmotic gases with osmotic stabilizing gases (or gas osmotic agents) are used to stabilize the resultant bubble
10 size distribution during and immediately after production. Upon generation of the bubbles, the higher LaPlace pressure in smaller bubbles causes diffusion through the liquid phase to the lower La Place pressure larger bubbles. This causes
15 the mean size distribution to increase above the capillary dimension limit of 5 microns over time. This is called disproportionation. When a mixture of a nonosmotic gas (e.g., air) is used with an osmotic vapor (e.g., C_6F_{14}) a slight reduction in volume of the smaller bubbles, due to air leaving the bubble, concentrates the osmotic gas and increases its osmotic pressure thus retarding further shrinkage while the larger bubbles increase in volume slightly, diluting the osmotic gas and retarding further growth.

25 An additional advantage of using a mixture of an extremely blood soluble gases (e.g., 87.5% by volume CO_2) and an osmotic gas mixture (e.g., 28% C_6F_{14} vapor + 72% air) is that, when injected, these bubbles rapidly shrink due to the loss of CO_2 to the blood. The bubbles, upon injection, will experience an 87.5% volume decrease due to loss of CO_2 . This
30 loss of CO_2 corresponds to a halving of the bubble diameter. Accordingly, one can prepare larger diameter bubbles (e.g., 9 μm), using simplified mechanical means, that will shrink to below 5 microns upon injection. In general, such bubbles will initially be prepared where the first gas is present in a ratio of at least 1:1 with respect to the second gas,

preferably at least 3:2, 2:1, 3:1, 4:1, 5:1, or 10:1. Where the microbubble membrane is more permeable to the first gas than to the second gas (e.g., the membrane has respective permeabilities to the gases in a ratio of at least about 2:1, 5
5 3:1, 4:1, 5:1, or 10:1, preferably even higher, e.g., 20:1, 40:1, or 100:1), the bubbles advantageously shrink from their original first diameter to an average second diameter of 75% or less of their original diameter quite rapidly (e.g., within one, two, four, or five minutes). Then, when at least 10 one relatively membrane-permeable gas is present in the aqueous medium surrounding the microbubble, the bubble is preferably stabilized at or about the second diameter for at least about 1 minute, preferably for 2, 3, 4, or 5 minutes. In one preferred embodiment, the bubbles maintain a size 15 between about 5 or 6 μm and 1 μm for at least 1, 2, 3, 4, or 5 minutes, stabilized by a gas osmotic pressure differential. The gas tension in the external liquid is preferably at least about 700 mm Hg. Moreover, a relatively membrane impermeable gas is also in the microbubble to create such an osmotic 20 pressure differential.

I. Microbubble Construction

A. The Aqueous or Other Liquid Phase

The external, continuous liquid phase in which the bubble resides typically includes a surfactant or foaming agent. Surfactants suitable for use in the present invention include any compound or composition that aids in the formation and maintenance of the bubble membrane by forming a layer at the interface between the phases. The foaming agent or surfactant may comprise a single compound or any 25 combination of compounds, such as in the case of co-surfactants. 30

Examples of suitable surfactants or foaming agents include: block copolymers of polyoxypropylene polyoxyethylene, sugar esters, fatty alcohols, aliphatic 35 amine oxides, hyaluronic acid aliphatic esters, hyaluronic acid aliphatic ester salts, dodecyl poly(ethyleneoxy)ethanol,

nonylphenoxy poly(ethyleneoxy)ethanol, hydroxy ethyl starch, hydroxy ethyl starch fatty acid esters, dextrans, dextran fatty acid esters, sorbitol, sorbitol fatty acid esters, gelatin, serum albumins, and combinations thereof.

5 In the present invention, preferred surfactants or foaming agents are selected from the group consisting of phospholipids, nonionic surfactants, neutral or anionic surfactants, fluorinated surfactants, which can be neutral or anionic, and combinations of such emulsifying or foaming
10 agents.

The nonionic surfactants suitable for use in the present invention include polyoxyethylene-polyoxypropylene copolymers. An example of such class of compounds is Pluronic, such as Pluronic F-68. Also contemplated are
15 polyoxyethylene fatty acids esters, such as polyoxyethylene stearates, polyoxyethylene fatty alcohol ethers, polyoxyethylated sorbitan fatty acid esters, glycerol polyethylene glycol oxystearate, glycerol polyethylene glycol ricinoleate, ethoxylated soybean sterols, ethoxylated castor oils, and the hydrogenated derivatives thereof, and cholesterol. Anionic surfactants, particularly fatty acids
20 (or their salts) having 12 to 24 carbon atoms, may also be used. One example of a suitable anionic surfactant is oleic acid, or its salt, sodium oleate.

25 It will be appreciated that a wide range of surfactants can be used. Indeed, virtually any surfactant or foaming agent (including those still to be developed) capable of facilitating formation of the microbubbles can be used in the present invention. The optimum surfactant or foaming agent
30 or combination thereof for a given application can be determined through empirical studies that do not require undue experimentation. Consequently, one practicing the art of the present invention should choose the surfactant or foaming agents or combination thereof based upon such properties as biocompatibility or their non-Newtonian
35 behavior.

The blood persistence of a contrast agent is inversely proportional to the LaPlace pressure which is proportional to the surface tension of the bubble. Reduced surface tension, therefore, increases blood persistence. Surfactants that
5 form ordered structures (multilaminar sheets and rods) in solution and produce non-Newtonian viscoelastic surface tensions are especially useful. Such surfactants include many of the sugar based surfactants and protein or glycoprotein surfactants (including bovine, human, or other
10 lung surfactants). One preferred type of such surfactant has a sugar or other carbohydrate head group, and a hydrocarbon or fluorocarbon tail group. A large number of sugars are known that can function as head groups, including glucose, sucrose, mannose, lactose, fructose, dextrose, aldose, and
15 the like. The tail group preferably has from about 2 or 4 to 20 or 24 carbon atoms, and may be, for example, a fatty acid group (branched or unbranched, saturated or unsaturated) covalently bound to the sugar through an ester bond. The surface tension of bubbles produced with these surfactants
20 greatly decreases as the surface is compressed by shrinkage of the bubble (e.g., when the bubble shrinks), and it is increased as the surface area of the bubble is increased (e.g., when the bubble grows). This effect retards disproportionation, which leads to narrower size distribution
25 and longer persisting bubbles in the vial and *in vivo*. A preferred surfactant mixture that has the properties associated with non-Newtonian viscoelasticity includes a nonionic surfactant or other foaming surfactant in combination with one of the non-Newtonian viscoelastic
30 surfactant such as one of the sugar esters (e.g. 2% Pluronic F-68 plus 1% sucrose stearate). Often the ratio of the nonionic surfactant to the non-Newtonian surfactant is from about 5:1 to about 1:5, with the surfactants together (whether non-Newtonian or more conventional) comprising 0.5
35 to 8%, more preferably about 1 to 5% (w/v) of the microbubble-forming liquid mixture.

The lowering of surface tension in small bubbles, counter to typical LaPlace pressure, allows the use of more efficient gas osmotic agents such as higher molecular weight perfluorocarbons as the gas osmotic agent. With conventional surfactants, the higher molecular weight PFCs will condense at the high bubble pressures. Without these efficient surfactants higher boiling less membrane permeable PFCs, e.g. C₆F₁₄, would be extremely difficult.

One may also incorporate other agents within the aqueous phase. Such agents may advantageously include conventional viscosity modifiers, buffers such as phosphate buffers or other conventional biocompatible buffers or pH adjusting agents such as acids or bases, osmotic agents (to provide isotonicity, hyperosmolarity, or hyposmolarity). Preferred solutions have a pH of about 7 and are isotonic. However, when CO₂ is used as a first gas in a bubble designed to shrink rapidly to a first size, a basic pH can facilitate rapid shrinkage by removing CO₂ as it leaves the bubble, preventing a buildup of dissolved CO₂ in the aqueous phase.

B. The Gas Phase

A major aspect of the present invention is in the selection of the gas phase. As was discussed above, the invention relies on the use of combinations of gases to harness or cause differentials in partial pressures and to generate gas osmotic pressures, which stabilize the bubbles. The primary modifier gas is preferably air or a gas present in air. Air and/or fractions thereof are also present in normal blood and serum. Where the microbubbles are to be used in an environment different from blood, the primary modifier gas is preferably selected from gases normally present in the external medium. Another criteria is the ease with which the primary modifier gas is diffused into or out of the bubbles. Typically, air and/or fractions thereof are also readily permeable through conventional flexible or rigid bubble surfaces. These criteria, in combination, allow for

the rapid diffusion of the primary modifier gas into or out of the bubbles, as required.

Modifier gases not present in the external medium can also be used. However, in this case the bubble will initially grow or shrink (depending on the relative permeability and concentrations of the external gases to the modifier) as the external gases replace the original modifier gas. If, during this process, the gas osmotic agent has not condensed, the bubble will remain stable.


The gas osmotic agent is preferably a gas that is less permeable through the bubble's surface than the modifier. It is also preferable that the gas osmotic agent is less soluble in blood and serum. Therefore, it will now be understood that the gas osmotic agent can be a gas at room or body temperature or it can ordinarily be a liquid at body temperature, so long as it has a sufficient partial or vapor pressure at the temperature of use to provide the desired osmotic effect.

Accordingly, fluorocarbons or other compounds that are not gases at room or body temperature can be used, provided that they have sufficient vapor pressure, preferably at least about 50 or 100 Torr at body temperature, or more preferably at least about 150 or 200 Torr. It should be noted that where the gas osmotic agent is a mixture of gases, the relevant measure of vapor pressure is the vapor pressure of the mixture, not necessarily the vapor pressure of the individual components of the mixed gas osmotic agent.

It is also important that where a perfluorocarbon is used as the osmotic agent within a bubble, the particular perfluorocarbon does not condense at the partial pressure present in the bubble and at body temperature. Depending on the relative concentrations of the primary modifier gas and the gas osmotic agent, the primary modifier gas may rapidly leave the bubble causing it to shrink and concentrate the secondary gas osmotic agent. Such shrinking may occur until the gas osmotic pressure equals the external pressure on the

bubble (maximum absolute arterial pressure) plus the LaPlace pressure of the bubble minus the air tension, or air saturation tension, of the blood (essentially one atmosphere). Thus the condensing partial pressure of the resulting gas mixture at 37°C must be above the equilibrium partial pressure, discussed above, of the osmotic agent.

5 Representative fluorocarbons meeting these criteria and in increasing ability to stabilize microbubbles are as follows:



Accordingly, it will be understood that PFC's with eight carbon atoms or fewer (37°C vapor pressures greater than 80 mm Hg) are preferred. As will also be understood, however, it is possible to construct larger molecules with increased 15 volatility through the addition of heteroatoms and the like. Therefore, the determination of the optimal secondary gas osmotic agent or gases agents is not size limited, but, rather, is based upon its ability to retain its vapor phase at body temperature and while providing a gas osmotic 20 pressure equal to at least the sum of the arterial and LaPlace pressures.

A listing of some compounds possessing suitable solubility and vapor pressure criteria is provided in Table I:

TABLE I

	perfluoro propanes, C_3F_8
	perfluoro butanes, C_4F_{10}
	perfluoro cyclo butanes, C_4F_8
5	perfluoro pentanes, C_5F_{12}
	perfluoro cyclo pentanes, C_5F_{10}
	perfluoro methylcyclobutanes, C_5F_{10}
	perfluoro hexanes, C_6F_{14}
	perfluoro cyclohexanes, C_6F_{12}
10	perfluoro methyl cyclopentanes, C_6F_{12}
	perfluoro dimethyl cyclobutanes, C_6F_{12}
	perfluoro heptanes, C_7F_{16}
	perfluoro cycloheptanes, C_7F_{14}
	perfluoro methyl cyclohexanes, C_7F_{14}
15	perfluoro dimethyl cyclopentanes, C_7F_{14}
	perfluoro trimethyl cyclobutanes, C_7F_{14}
	perfluoro triethylamines, $N(C_2F_5)_3$

It will be appreciated that one of ordinary skill in the art can readily determine other compounds that would perform suitably in the present invention that do not meet both the solubility and vapor pressure criteria, described above. Rather, it will be understood that certain compounds can be considered outside the preferred range in either solubility or vapor pressure, if such compounds compensate for the aberration in the other category and provide a superior insolubility or low vapor pressure.

It should also be noted that for medical uses the gases, both the modifier gas and the gas osmotic agent, should be biocompatible or not be physiologically deleterious. Ultimately, the microbubbles containing the gas phase will decay and the gas phase will be released into the blood either as a dissolved gas or as submicron droplets of the condensed liquid. It will be understood that gases will primarily be removed from the body through lung respiration

or through a combination of respiration and other metabolic pathways in the reticuloendothelial system.

Appropriate gas combinations of the primary modifier and secondary gases can be ascertained empirically without undue 5 experimentation. Such empirical determinations are described in the Examples.

When an efficient surfactant, e.g., bovine lung surfactant, is employed to produce a large diameter bubble with a low surface tension, the LaPlace pressure is very low. 10 When perfluoroctylbromide (PFOB) saturated air is inside the bubble and the bubble is exposed to air or a liquid nearly saturated with air (e.g., equilibrated with air) the gas osmotic pressure is greater than the LaPlace pressure and therefore the bubble grows. With smaller diameter bubbles 15 the LaPlace pressure is higher and therefore the bubble shrinks and collapses. This shrinkage is at a reduced rate being driven by the difference between the LaPlace pressure minus reduced by the gas osmotic pressure. When small diameter bubbles are created by sonicating gas or gas vapor 20 mixtures in a low surface tension surfactant solution, e.g., 2% pluronic F-68 plus 1% sucrose stearate, the time the bubbles persist *in vitro*, as observed by microscope, and *in vivo* as observed by Doppler ultrasound imaging of a rabbit's 25 kidney post intravenous injection, correlated with the above gas osmotic pressure comparison.

In the rabbit kidney Doppler experiment (Example III), contrast enhancement was observed for up to 10 minutes with perfluorohexane/air mixtures in the bubbles compared with the instantaneous disappearance of contrast with pure air 30 microbubbles. Thus, these perfluorochemicals are capable of exerting gas osmotic pressures that nearly counterbalance the LaPlace pressure and create functional ultrasound microbubble contrast agents.

A surprising discovery was that mixtures of PFCs, e.g., 35 C_4F_{10} (as a combination modifier gas and a gas osmotic agent) saturated with C_6F_{14} vapor (as the main gas osmotic agent),

can stabilize the bubble for longer times than either component alone. This is because C_4F_{10} is a gas at body temperature (and, thus, can act as both a modifier gas and a gas osmotic agent) has a somewhat reduced membrane permeability and it is only slightly soluble in C_6F_{14} at body temperature. In this situation the gas osmotic pressures of both agents are added together, leading to increased bubble persistence over that of air/ C_6F_{14} only mixtures. It is possible that the condensing point of the longer persisting higher molecular weight C_6F_{14} component is increased, allowing a larger maximum gas osmotic pressure to be exerted. Other mixtures of PFCs will perform similarly. Preferred mixtures of PFCs will have ratios of 1:10 to 10:1, and include such mixtures as perfluorobutane/perfluorohexane and perfluorobutane/perfluoropentane. These preferred fluorocompounds can be branched or straight chain.

As was discussed above, we have also discovered that mixtures of nonosmotic gases in combination with the gas osmotic agent act to stabilize the size distribution of the bubbles before and after injection. Upon generation of the bubbles, the higher LaPlace pressures in smaller bubbles causes diffusion through the liquid phase to the lower LaPlace pressure larger bubbles. This causes the mean size distribution to increase above the capillary dimension limit of 5 microns with time. This is called disproportionation.

However, when a mixture of a modifier gases (e.g., air or carbon dioxide) are used with a gas osmotic agent (e.g., C_6F_{14}) a slight reduction in volume of the smaller bubbles, due to one of the modifier gases leaving the bubble, will concentrate the osmotic gas and increases its osmotic pressure, thus, retarding further shrinkage. On the other hand, the larger bubbles will increase in volume slightly, diluting the osmotic gas and also retarding further growth.

An additional advantage of using a mixture of an extremely blood soluble gas (e.g., 75% through 87.5% by volume CO_2) and an osmotic gas mixture (e.g. 28% C_6F_{14} vapor

and 72% air) is that when injected, these bubbles rapidly shrink due to the loss of CO₂ to the blood. Carbon dioxide leaves particularly fast due to a specific plasma enzyme that catalyzes its dissolution. An 87.5% volume decrease due to
5 loss of CO₂ corresponds with a halving of the bubble diameter. Accordingly, larger can be produced which will shrink to an appropriate size (i.e., 5 microns) upon injection or exposure to a solution with a basic or alkaline pH.

10 Accordingly, we have discovered that through use of a gas that is relatively hydrophobic and that has a relatively low membrane permeability, the rate of contrast particle decay can be reduced. Thus, through reducing the particle decay rate, the microbubbles' half lives are increased and
15 contrast enhancement potential is extended.

II. Other Components.

It will be understood that other components can be included in the microbubble formulations of the present invention. For example, osmotic agents, stabilizers,
20 chelators, buffers, viscosity modulators, air solubility modifiers, salts, and sugars can be added to fine tune the microbubble suspensions for maximum life and contrast enhancement effectiveness. Such considerations as sterility, isotonicity, and biocompatibility may govern the use of such conventional additives to injectable compositions. The use
25 of such agents will be understood to those of ordinary skill in the art and the specific quantities, ratios, and types of agents can be determined empirically without undue experimentation.

30 III. Formation of the Microbubbles of the Present Invention.

There are a variety of methods to prepare microbubbles in accordance with the present invention. Sonication is preferred for the formation of microbubbles, i.e., through an ultrasound transmitting septum or by penetrating a septum
35 with an ultrasound probe including an ultrasonically vibrating hypodermic needle. However, it will be appreciated

that a variety of other techniques exist for bubble formation. For example, gas injection techniques can be used, such as venturi gas injection.

Other methods for forming microbubbles include formation of particulate microspheres through the ultrasonication of albumin or other protein as described in European Patent Application 0,359,246 by Molecular Biosystems, Inc.; the use of tensides and viscosity increasing agents as described in U.S. Patent No. 4,446,442; lipid coated, non-liposomal, microbubbles as is described in U.S. Patent No. 4,684,479; liposomes having entrapped gases as is described in U.S. Patent Nos. 5,088,499 and 5,123,414; and the use of denatured albumin particulate microspheres as is described in U.S. Patent No. 4,718,433. The disclosure of each of the foregoing patents and applications is hereby incorporated by reference.

Any of the above methods can be employed with similar success to entrain the modifier gases and gas osmotic agents of the present invention. Moreover, it is expected that similar enhancement in longevity of the bubbles created will be observed through use of the invention.

Sonication can be accomplished in a number of ways. For example, a vial containing a surfactant solution and gas in the headspace of the vial can be sonicated through a thin membrane. Preferably, the membrane is less than about 0.5 or 0.4 mm thick, and more preferably less than about 0.3 or even 0.2 mm thick, i.e., thinner than the wavelength of ultrasound in the material, in order to provide acceptable transmission and minimize membrane heating. The membrane can be made of materials such as rubber, Teflon, mylar, urethane, aluminized film, or any other sonically transparent synthetic or natural polymer film or film forming material. The sonication can be done by contacting or even depressing the membrane with an ultrasonic probe or with a focused ultrasound "beam." The ultrasonic probe can be disposable. In either event, the probe can be placed against or inserted through the membrane

and into the liquid. Once the sonication is accomplished, the microbubble solution can be withdrawn from and vial and delivered to the patient.

5 Sonication can also be done within a syringe with a low power ultrasonically vibrated aspirating assembly on the syringe, similar to an inkjet printer. Also, a syringe or vial may be placed in and sonicated within a low power ultrasonic bath that focuses its energy at a point within the container.

10 Mechanical formation of microbubbles is also contemplated. For example, bubbles can be formed with a mechanical high shear valve (or double syringe needle) and two syringes, or an aspirator assembly on a syringe. Even simple shaking may be used. The shrinking bubble techniques 15 described herein are particularly suitable for mechanically formed bubbles, having lower energy input than sonicated bubbles. Such bubbles will typically have a diameter much larger than the ultimately desired biocompatible imaging agent, but can be made to shrink to an appropriate size in 20 accordance with the present invention.

In another method, microbubbles can be formed through the use of a liquid osmotic agent emulsion supersaturated with a modifier gas at elevated pressure introduced into in 25 a surfactant solution. This production method works similarly to the opening of soda pop, where the gas foams upon release of pressure forming the bubbles.

In another method, bubbles can be formed similar to the foaming of shaving cream, where perfluorobutane, freon, or another like material that boils when pressure is released. 30 However, in this method it is imperative that the emulsified liquid boils sufficiently low or that it contain numerous bubble nucleation sites so as to prevent superheating and supersaturation of the aqueous phase. This supersaturation will lead to the generation of a small number of large 35 bubbles on a limited number of nucleation sites rather than

the desired large number of small bubbles (one for each droplet).

In still another method, dry void-containing particles or other structures (such as hollow spheres or honeycombs) that rapidly dissolve or hydrate, preferably in an aqueous solution, e.g., albumin, microfine sugar crystals, hollow spray dried sugar, salts, hollow surfactant spheres, dried porous polymer spheres, dried porous hyaluronic acid, or substituted hyaluronic acid spheres, or even commercially available dried lactose microspheres can be stabilized with a gas osmotic agent.

For example, a spray dried surfactant solution can be formulated to obtain 5 micron or larger hollow spheres and packaged in a vial filled with an osmotic gas or a desired gas mixture as described herein. The gas will diffuse into the spheres. Diffusion can be aided by pressure or vacuum cycling. When reconstituted with a sterile solution the spheres will rapidly dissolve and leave osmotic gas stabilized bubbles in the vial. In the alternative, a lyophilized cake of surfactant and bulking reagents produced with a fine pore structure can be placed in a vial with a sterile solution and a head spaced with an osmotic gas mixture. The solution can be frozen rapidly to produce a fine ice crystal structure and, therefore, upon lyophilization produces fine pores (voids where the ice crystals were removed).

Alternatively, any dissolvable or soluble void-forming structures may be used. In this embodiment, where the void-forming material is not made from or does not contain surfactant, both surfactant and liquid are supplied into the container with the structures and the desired gas or gases. Upon reconstitution these voids trap the osmotic gas and, with the dissolution of the solid cake, form microbubbles with the gas or gases in them.

It will be appreciated that kits can be prepared for use in making the microbubble preparations of the present

265000 240000 100000

invention. These kits can include a container enclosing the gas or gases described above for forming the microbubbles, the liquid, and the surfactant. Alternatively, the container can contain the void forming material and the gas or gases, 5 and the surfactant and liquid can be added to form the microbubbles. Alternatively, the surfactant can be present with the other materials in the container, and only the liquid needs to be added in order to form the microbubbles. Where a material necessary for forming the microbubbles is 10 not already present in the container, it can be packaged with the other components of the kit, preferably in a form or container adapted to facilitate ready combination with the other components of the kit.

The container used in the kit may be of the type 15 described elsewhere herein. In one embodiment, the container is a conventional septum-sealed vial. In another, it has a means for directing or permitting application of sufficient bubble forming energy into the contents of the container. This means can comprise, for example, the thin web or sheet 20 described previously.

Any of the microbubble preparations of the present invention may be administered to a vertebrate, such as a bird or a mammal, as a contrast agent for ultrasonically imaging portions of the vertebrate. Preferably, the vertebrate is a 25 human, and the portion that is imaged is the vasculature of the vertebrate. In this embodiment, a small quantity of microbubbles (e.g., 0.1 ml/Kg based on the body weight of the vertebrate) is introduced intravascularly into the animal. Other quantities of microbubbles, such as from about 0.005 30 ml/Kg to about 1.0 ml/Kg, can also be used. Imaging of the heart, arteries, veins, and organs rich in blood, such as liver, lungs, and kidneys can be ultrasonically imaged with this technique.

The foregoing description will be more fully understood 35 with reference to the following Examples. Such Examples, are, however, exemplary of preferred methods of practicing

the present invention and are not limiting of the scope of the invention or the claims appended hereto.

Example I

5 Preparation of microbubbles through sonication

Microbubbles with an average number weighted size of 5 microns were prepared by sonication of an isotonic aqueous phase containing 2% Pluronic F-68 and 1% sucrose stearate as surfactants, air as a modifier gas and perfluorohexane as the gas osmotic agent.

In this experiment, 1.3 ml of a sterile water solution containing 0.9% NaCl, 2% Pluronic F-68 and 1% sucrose stearate was added to a 2.0 ml vial. The vial had a remaining head space of 0.7 ml initially containing air. Air saturated with perfluorohexane vapor (220 torr of perfluorohexane with 540 torr of air) at 25 degrees C was used to flush the headspace of the vial. The vial was sealed with a thin 0.22 mm polytetrafluoroethylene (PTFE) septum. The vial was turned horizontally, and a 1/8" (3 mm) sonication probe attached to a 50 watt sonicator model VC50, available from Sonics & Materials was pressed gently against the septum. In this position, the septum separates the probe from the solution. Power was then applied to the probe and the solution was sonicated for 15 seconds, forming a white solution of finely divided microbubbles, having an average number weighted size of 5 microns as measured by Horiba LA-700 laser light scattering particle analyzer.

30 Example II

Measurement of in-vitro size of microbubbles

The in-vitro size of the microbubbles prepared in Example I was measured by laser light scattering. Studies of bubbles 35 were conducted where the microbubbles were diluted into a 4% dextrose water solution (1:50) circulating through a Horiba

LA-700 laser light scattering analyzer. The average microbubbles size was 5 microns and doubled in size in 25 minutes.

Interestingly, microbubbles prepared through the same method in Example I without the use of a gas osmotic agent (substituting air for the perfluorohexane / air mixture) had an average size of 11 microns and gave only background readings on the particle analyzer at 10 seconds.

10

Example III

Measurement of in-vivo lifetime of microbubbles

15

20

The lifetimes of microbubbles prepared in accordance with Example I were measured in rabbits through injecting 0.2 ml of freshly formed microbubbles into the marginal ear vein of a rabbit that was under observation with a Accuson 128XP/5 ultrasound imaging instrument with a 5 megahertz transducer. Several tests were conducted, during which images of the heart, inferior vena cava/aorta, and kidney were obtained while measuring the time and extent of the observable contrast enhancement. The results are presented in the following Table II:

Table II

25

ORGAN	DOSE	TIME MAX. INTENSITY	TIME TO MINIMUM USABLE INTENSITY	TIME TO NO ENHANCEMENT
Heart	0.1 ml/Kg	7-10 sec.	8-10 min.	25 min.
IVC/Aorta	0.1 ml/Kg	7-10 sec.	8-10 min.	25 min.
Kidney	0.1 ml/Kg	7-10 sec.	8-10 min.	25 min.

30

In Table III, a comparison of microbubbles prepared in an identical fashion without the use of an osmotic gas is presented (only air was used). Note that sporadic reflections were observed only in the right heart ventricle during the injection but disappeared immediately post dosing.

Table III

5

ORGAN	DOSE	TIME TO MAXIMUM INTENSITY	TIME TO MINIMUM USABLE INTENSITY	TIME TO NO ENHANCEMENT
Heart	0.1 mL/Kg	0	0	0
IVC/Aorta	0.1 mL/Kg	0	0	0
Kidney	0.1 mL/Kg	0	0	0

10 The use of an osmotic or gas osmotic agent dramatically increased the length of time for which microbubbles are visible.

Example IV

Preparation of mixed osmotically stabilized microbubbles

15 Microbubbles with an average number weighted size of 5 microns were prepared by sonication of an isotonic aqueous phase containing 2% Pluronic F-68 and 1 % sucrose stearate as surfactants and mixtures of perfluorohexane and perfluorobutane as the gas osmotic agents.

20 In this experiment, 1.3 ml of a sterile water solution containing 0.9% NaCl and 2% Pluronic F-68 was added to a 2.0 ml vial. The vial had a remaining head space of 0.7 ml, initially containing air. An osmotic gas mixture of perfluorohexane, 540 Torr and perfluorobutane at 220 Torr was 25 used to flush the headspace before sealing with a thin 0.22 mm PTFE septum. The vial was sonicated as in Example I, forming a white solution of finely divided microbubbles, having an average particle size of 5 microns as measured by a Horiba LA-700 laser light scattering particle analyzer. 30 This procedure was repeated twice more, once with pure perfluorobutane and then with a 540 Torr air + 220 Torr perfluorohexane mixture. Vascular persistence of all three preparations was determined by ultrasound imaging of a rabbit post I.V. injection and are listed below

1.5 minutes perfluorobutane
2 minutes perfluorohexane + air
3 minutes perfluorobutane + perfluorohexane

5 The mixture of perfluorocarbons persisted longer than either agent alone.

Example V

10 Preparation of gas osmotically stabilized microbubbles from soluble spray dried spheres

Gas osmotically stabilized microbubbles were prepared by dissolving hollow spray dried lactose spheres, filled with an air perfluorohexane vapor mixture, in a surfactant solution.

15 Spray dried spheres of lactose with a mean diameter of approximately 100 micron and containing numerous 10 to 50 micron cavities, was obtained from DMV International under the trade name of Pharmatose DCL-11. Ninety milligrams of the lactose spheres was placed in a 2.0 ml vial. The porous spheres were filled with a mixture of 220 Torr perfluorohexane and 540 Torr air by cycling the gas pressure in the vial between one atmosphere and 1/2 atmosphere a total of 12 times over 5 minutes. A surfactant solution containing 0.9% sodium chloride, 2% Pluronic-F68 and 1% sucrose stearate was warmed to approximately 45°C, to speed the dissolution of the lactose, before injecting 1.5 ml of the warmed solution into the vial. The vial was then gently agitated by inversion for approximately 30 seconds to dissolve the lactose before injecting the microbubbles thus prepared into the Horiba LA-700 particle analyzer. A 7.7 micron volume weighted median diameter was measured approximately one minute after dissolution. The diameter of these microbubbles remained nearly constant, changing to a median diameter of 7.1 microns in 10 minutes. When the experiment was repeated 20 with air filled lactose, the particle analyzer gave only background readings one minute after dissolution, thus 25 30 35

demonstrating that gas osmotically stabilized microbubbles can be produced by the dissolution of gas-filled cavity-containing structures.

Example VI

5 Preparation of larger bubbles that shrink to a desired size

Microbubbles with an average volume weighted size of 20 microns shrinking to 2 microns were prepared by sonication of an isotonic aqueous phase containing 2% Pluronic F-68 as the 10 surfactant, CO₂ as a diluent gas and perfluorohexane as the gas osmotic agent.

In this experiment, 1.3 ml of a sterile water solution containing 0.9% NaCl, 2% Pluronic F-68 and 1 % sucrose stearate was added to a 2.0 ml vial. The vial had a 15 remaining head space of 0.7 ml initially containing air. A mixture of air saturated with perfluorohexane at 25 degrees C diluted by a factor of 10 with CO₂ (684 Torr CO₂ + 54 Torr air + 22 Torr perfluorohexane) was used to flush the head space. The vial was sealed with a thin 0.22 mm PTFE septum. 20 The vial was sonicated as in Example I, forming a white solution of finely divided microbubbles, having an average particle size of 28 microns as measured by Horiba LA-700 laser light scattering analyzer. In the 4% dextrose + 0.25mM NaOH solution of the Horiba, the average bubble diameter 25 rapidly shrank in 2 to 4 minutes from 28 microns to 5 to 7 microns, and then remained relatively constant , reaching 2.6 micron after 27 minutes. This is because the CO₂ leaves the microbubbles by dissolving into the water phase.

30 Example VII

Perfluoroheptane stabilized microbubble *in vitro* experiment

Microbubbles were prepared as in Example I above employing perfluoroheptane saturated air (75 torr plus 685 35 torr air) and were measured as in Example II above. The average number weighted diameter of these microbubbles was

7.6 micron, one minute after circulation, and 2.2 microns after 8 minutes of circulation. This persistence, compared to the near immediate disappearance of microbubbles containing only air, demonstrates the gas osmotic
5 stabilization of perfluoroheptane.

Example VIII

Perfluorotripropyl amine stabilized microbubble *in vivo* experiment

10 Microbubbles were prepared as in Example I above, employing perfluorotripropyl amine saturated air and were assessed as in Example III above. The usable vascular persistence of these microbubbles was found to be 2.5 minutes, thus demonstrating the gas osmotic stabilization
15 of perfluorotripropyl amine.

Example IX

Effect of a non Newtonian viscoelastic surfactant - sucrose stearate

20 Microbubbles were prepared as in Example I above employing 0.9% NaCl, 2% Pluronic F-68 and 2% sucrose stearate as the surfactant and with perfluoropropane saturated air and perfluorohexane saturated air in the
25 headspace. These two preparations were repeated with the same surfactant solution minus sucrose stearate. All four microbubble preparations were assessed as in Example III above. The usable vascular persistence of these microbubbles are listed below:

2% Pluronic F-68 + 2% sucrose stearate persistence

2 minutes perfluoropropane

4 minutes perfluorohexane

5

2% Pluronic F-68 only persistence

2 minutes perfluoropropane

1 minute perfluorohexane

As seen above, the reduced surface tension made
possible by the non-Newtonian viscoelastic properties of
sucrose stearate prevented the less volatile
perfluorohexane from condensing, allowing perfluorohexane
microbubbles of longer persistence to be produced.

15

The foregoing description details certain preferred
embodiments of the present invention and describes the best
mode contemplated. It will be appreciated, however, that
no matter how detailed the foregoing appears in text, the
invention can be practiced in many ways and the invention
should be construed in accordance with the appended Claims
and any equivalents thereof.

WHAT IS CLAIMED IS:

1. A stabilized gas filled microbubble preparation, comprising:

5 a mixture of a first gas or gases and a second gas or gases within generally spherical membranes to form microbubbles, wherein said first gas and said second gas are respectively present in a molar ratio of about 1:100 to about 1000:1, and wherein said first gas has a vapor pressure of at least about $(760 - x)$ mm Hg at 37°C , where x is the vapor pressure of the
10 second gas at 37°C , and wherein said vapor pressure of each of said first and second gases is greater than about 75 mm Hg at 37°C , with the proviso that said first gas and said second gas are not water vapor.

15 2. The preparation of Claim 1, wherein said second gas comprises a fluorocarbon and said first gas is a nonfluorocarbon.

3. The preparation of Claim 2, wherein said first gas comprises nitrogen, oxygen, carbon dioxide, or a mixture thereof.

20 4. The preparation of Claim 2, wherein:
said microbubbles are in a liquid medium and have a first average diameter;
the ratio of said first gas to said second gas in said microbubbles is at least 1:1; and

25 5. said microbubbles are adapted to shrink in said medium as a result of loss of said first gas through said membrane to a second average diameter of less than about 75% of said first diameter and then remain stabilized at or about said second diameter for at least about 1 minute as a result of a gas osmotic pressure differential across said membrane.

30 5. The preparation of Claim 4, wherein said medium is aqueous.

6. The preparation of Claim 4, wherein said medium is in a container and said microbubbles have been formed in said container.

5 7. The preparation of Claim 4, wherein said medium is blood *in vivo*.

10 8. The preparation of Claim 4, wherein said liquid medium contains gas or gases dissolved therein with a gas tension of at least about 700 mm Hg, wherein said first diameter is at least about 5 μm , and wherein the tension of the gas or gases dissolved in said medium is less than the pressure of the same gas or gases inside said microbubbles.

15 9. The preparation of Claim 4, wherein said first diameter is at least about 10 μm and said second diameter is between about 1 μm and 6 μm .

10. The preparation of Claim 1, wherein said second gas has an average molecular weight at least about 4 times that of said first gas.

20 11. The preparation of Claim 1, wherein said second gas has a vapor pressure less than about 750 mm Hg at 37°C.

12. The preparation of Claim 11, wherein said molar ratio of said first gas to said second gas is from about 1:10 to about 500:1.

25 13. The preparation of Claim 11, wherein said second gas comprises a fluorocarbon and said first gas is a nonfluorocarbon.

14. The preparation of Claim 13, wherein said second gas comprises at least two fluorocarbons.

30 15. The preparation of Claim 13, wherein said second gas comprises a perfluorocarbon.

16. The preparation of Claim 11, wherein both said first gas and said second gas comprise fluorocarbons.

17. The preparation of Claim 1, wherein said microbubbles contain as said first gas, or as said second gas, or respectively as said first and second gases,

gaseous perfluorobutane and perfluorohexane in a ratio from about 1:10 to about 10:1.

18. The preparation of Claim 1, wherein said
microbubbles contain as said first gas, or as said second
gas, or respectively as said first and second gases,
gaseous perfluorobutane and perfluoropentane in a ratio
from about 1:10 to about 10:1.

19. The preparation of Claim 1, wherein said second
gas has a water solubility of not more than about 0.5 mM at
25°C and one atmosphere, and wherein said first gas has a
water solubility at least about 10 times greater than that
of said second gas.

20. The preparation of Claim 1, wherein the
permeability of the membrane to said first gas is at least
about 5 times greater than the permeability of said
membrane to said second gas.

21. The preparation of Claim 1, further comprising:
a container enclosing said microbubbles; and
a liquid in said container in admixture with said
microbubbles, wherein said container further comprises
means for transmission of sufficient ultrasonic energy
to said liquid to permit formation of said
microbubbles by sonication.

22. The preparation of Claim 21, wherein said means
for transmission comprises a flexible polymer material
having a thickness less than about 0.5 mm.

23. The preparation of Claim 1, wherein said membrane is a surfactant.

24. The preparation of Claim 23, wherein said
30 surfactant comprises a non-Newtonian viscoelastic
surfactant.

25. The preparation of Claim 23, wherein said surfactant is a carbohydrate.

26. The preparation of Claim 25, wherein said
carbohydrate is a polysaccharide.

27. The preparation of Claim 23, wherein said surfactant is a fatty acid ester of a sugar.

28. The preparation of Claim 23, wherein said surfactant is sucrose stearate.

5 29. The preparation of Claim 23, wherein said surfactant is proteinaceous.

30. The preparation of Claim 1, wherein said membrane is solid or semi-solid.

10 31. The preparation of Claim 1, wherein said membrane is a proteinaceous material.

32. The preparation of Claim 30, wherein said proteinaceous material is albumin.

33. A kit for use in preparing microbubbles, comprising:

15 a sealed container;
a liquid in said container;
a surfactant in said container; and
a fluorocarbon gas in said container, wherein
said liquid, said surfactant, and said fluorocarbon
gas or vapor are together adapted to form microbubbles
20 upon the application of energy thereto.

34. The kit of Claim 33, further comprising
means in said container for permitting
transmission of sufficient external ultrasonic energy
25 to said liquid to form microbubbles in said container.

35. The kit of Claim 34, wherein said means for
transmission comprises a flexible polymer membrane having a
thickness less than about 0.5 mm.

30 36. The kit of Claim 33, further comprising:
a nonfluorocarbon gas in said container, wherein
the molar ratio of said nonfluorocarbon gas to said
fluorocarbon gas is from about 1:10 to about 1000:1,
with the proviso that said nonfluorocarbon gas is not
water vapor.

35 37. A kit for use in preparing microbubbles,
comprising:

a container;

dried liquid-soluble void-containing structures
in said container, said void-containing structures
defining a plurality of voids having an average
diameter less than about 100 μm ;

5

a gas in said voids; and

10

a surfactant, wherein said void-containing
structures, said gas, and said surfactant are together
adapted to form microbubbles upon addition to said
container of a liquid in which said void-containing
structures are soluble.

38. The kit of Claim 37, wherein said void-containing
structures comprise at least in part said surfactant.

15

39. The kit of Claim 37, wherein said surfactant is a
non-Newtonian viscoelastic surfactant.

20

40. The kit of Claim 37, wherein said surfactant is a
fatty acid ester of a sugar.

25

41. The kit of Claim 37, wherein said surfactant is
sucrose stearate.

42. The kit of Claim 37, wherein said void-containing
structures are proteinaceous.

43. The kit of Claim 37, wherein said void-containing
structures are formed of a carbohydrate.

25

44. A method for forming microbubbles, comprising the
steps of:

30

35

providing a first gas, a second gas, a membrane
forming material, and a liquid, wherein said first gas
and said second gas are present in a molar ratio of
about 1:100 to about 1,000:1, and wherein said first
gas has a vapor pressure of at least about (760 - x)
mm Hg at 37°C, where x is the vapor pressure of the
second gas at 37°C, and wherein said vapor pressure of
each of said first and second gases is greater than
about 75 mm Hg at 37°C, with the proviso that said
first gas and said second gas are not water vapor; and

surrounding said first and second gases with said membrane forming material to form microbubbles in said liquid.

45. The method of Claim 44, wherein said membrane forming material is a surfactant.

46. The method of Claim 44, further comprising the steps of:

initially forming microbubbles having a first average diameter wherein the initial ratio of said first gas to said second gas in said microbubbles is at least about 1:1;

contacting said microbubbles having a first average diameter with a liquid medium;

shrinking said microbubbles in said medium as a result of loss of said first gas through said membrane; and then

stabilizing said microbubbles at a second average diameter of less than about 75% of said first diameter for a period of at least one minute.

47. The method of Claim 46, wherein said microbubbles are stabilized at said second diameter by:

providing a gas osmotic pressure differential across said membrane such that the tension of a gas or gases dissolved in said medium is equal to or greater than the partial pressure of the same gas or gases inside said microbubbles.

48. The method of Claim 47, wherein said first diameter is at least about 5 μm .

49. A method for forming microbubbles, comprising the steps of:

providing dried liquid-soluble void-containing structures, said void-containing structures defining a plurality of voids having a diameter less than about 100 μm ;

35 providing a gas in said voids;
providing a surfactant;

C

providing said void-containing structures, said
gas, and said surfactant in admixture with a liquid in
which said void-containing structures are soluble; and
dissolving said void-containing structures in

5 said liquid whereby the gas in said enclosures forms
microbubbles that are surrounded by said surfactant.

50. The method of Claim 49, wherein said membrane
structures are microspheres.

51. The method of Claim 49, wherein said microbubbles
10 contain a first gas and a second gas respectively present
in a molar ratio of from about 1:100 to about 1000:1.

52. A method for imaging an object or body,
comprising the steps of:

15 introducing into said object or body a
microbubble preparation according to Claim 1; and then
ultrasonically imaging at least a portion of said
object or body.

53. The method of Claim 52, wherein said body is a
vertebrate and said preparation is introduced into the
20 vasculature of said vertebrate.

54. The method of Claim 52, wherein said preparation
is a preparation as defined in Claim 2.

55. The method of Claim 52, wherein said preparation
is a preparation as defined in Claim 4.

25 56. The method of Claim 52, wherein said preparation
is a preparation as defined in Claim 7.

57. The method of Claim 52, wherein said preparation
is a preparation as defined in Claim 10.

30 58. The method of Claim 52, further comprising the
step of preparing said microbubble preparation prior to
said introduction according to the method of Claim 44.

59. The method of Claim 52, further comprising the
step of preparing said microbubble preparation prior to
said introduction according to the method of Claim 46.

60. The method of Claim 52, further comprising the step of preparing said microbubble preparation prior to said introduction according to the method of Claim 47.

5 61. The method of Claim 52, further comprising the step of preparing said microbubble preparation prior to said introduction according to the method of Claim 49.

STABILIZED MICROBUBBLE COMPOSITIONS

ABSTRACT

A microbubble preparation formed of a plurality of
5 microbubbles comprising a first gas and a second gas
surrounded by a membrane such as a surfactant, wherein the
first gas and the second gas are present in a molar ratio
of from about 1:100 to about 1000:1, and wherein the first
gas has a vapor pressure of at least about $(760 - x)$ mm Hg
10 at 37°C, where x is the vapor pressure of the second gas at
37°C, and wherein the vapor pressure of each of the first
and second gases is greater than about 75 mm Hg at 37°C;
also disclosed are methods for preparing microbubble
15 compositions, including compositions that rapidly shrink
from a first average diameter to a second average diameter
less than about 75% of the first average diameter and are
stabilized at the second average diameter; kits for
preparing microbubbles; and methods for using such
microbubbles as ultrasound contrast agents.

20

25 CAH-3286.d:NI
072893

DECLARATION AND POWER OF ATTORNEY - USA PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled **STABILIZED MICROBUBBLE COMPOSITIONS**; the specification of which is attached hereto;

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above;

I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56;

POWER OF ATTORNEY: I hereby appoint the following attorneys and/or agents to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith (if this application is assigned, I acknowledge that the appointed individuals do not represent me, and that instead they represent the assignee): Louis J. Knobbe, Registration No. 18,780; Don W. Martens, Registration No. 21,107; Gordon H. Olson, Registration No. 20,319; James B. Bear, Registration No. 25,221; Darrell L. Olson, Registration No. 28,247; William B. Bunker, Registration No. 29,365; William H. Nieman, Registration No. 30,201; John C. Lambertsen, Registration No. 29,400; Lowell Anderson, Registration No. 30,990; Arthur S. Rose, Registration No. 28,038; James F. Lesniak, Registration No. 25,240; Ned A. Israelsen, Registration No. 29,655; Drew S. Hamilton, Registration No. 29,801; Jerry T. Sewell, Registration No. 31,567; John B. Sganga, Jr., Registration No. 31,302; Edward A. Schlatter, Registration No. 32,297; Gerard von Hoffmann, Registration No. 33,043; William C. Rookridge, Registration No. 31,791; Joseph R. Re, Registration No. 31,291; John M. Carson, Registration No. 34,303; Andrew H. Simpson, Registration No. 31,469; Daniel E. Altman, Registration No. 34,115; Anita M. Kirkpatrick, Registration No. 32,617; Vito A. Canuso, Registration No. 35,471; William H. Shreve, Registration No. 35,678; Stephen C. Jensen, Registration No. 35,556; Michael Fedrick, Registration No. 36,799; Nancy Ways Vensko, Registration No. 36,298; Myra H. McCormack, Registration No. 36,602; Renee E. Rogers, Registration No. 36,657; Guy L. Cumberbatch, Registration No. 36,114; Michael L. Fuller, Registration No. 36,516; and George T. Parsons, Registration No. 34,690.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and

belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful, false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor: Ernest G. Schutt

Inventor's signature Unsigned

Date 7/30/93

Residence: San Diego, California

Citizenship: United States of America

Post Office Address: 12139 Ragweed Street, San Diego, California 92129

Full name of second inventor: David P. Evitts

Inventor's signature Unsigned

Date 7/30/93

Residence: La Jolla, California

Citizenship: United States of America

Post Office Address: 8440-C Via Mallorca, La Jolla, California 92037

Full name of third inventor: Rene Alta Kinner

Inventor's signature Unsigned

Date 7/30/93

Residence: San Diego, California

Citizenship: United States of America

Post Office Address: 3955 3rd Avenue, San Diego, California 92103

DEPT OF STATE - PLEADING

Full name of fourth inventor: Charles David Anderson

Inventor's signature

Date 7/30/93

Residence: Lebanon, New Jersey

Citizenship: United States of America

Post Office Address: 27 Potterstown Road, Lebanon, New Jersey 08833

Full name of fifth inventor: Jeffry G. Weers

Inventor's signature

Date 7/30/93

Residence: San Diego, California

Citizenship: United States of America

Post Office Address: 12191 Salix Way, San Diego, California 92129

Send Correspondence To:
KNOBBE, MARTENS, OLSON & BEAR
620 Newport Center Drive
Sixteenth Floor
Newport Beach, CA 92660-8016

Direct Telephone Calls To:
Ned A. Israelsen
(619) 235-8550

NAI-4689/krs

COPY

DECLARATION - USA PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled STABILIZED MICROBUBBLE COMPOSITIONS; the specification of which was filed on July 30, 1993 as Application Serial No. 08/099,951.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above;

I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56;

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful, false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor: Ernest G. Schutt

Inventor's signature Ernest G. Schutt

Date Sept. 28, 1993

Residence: San Diego, California

Citizenship: United States of America

Post Office Address: 12139 Ragweed Street, San Diego, California 92129

Full name of second inventor: David P. Evitts

Inventor's signature David P. Evitts

Date Sept 29, 1993

Residence: La Jolla, California

Citizenship: United States of America

Post Office Address: 8440-C Via Mallorca, La Jolla, California
92037

Full name of third inventor: Rene Alta Kinner

Inventor's signature Rene Alta Kinner

Date Sept 28, 1993

Residence: San Diego, California

Citizenship: United States of America

Post Office Address: 3955 Third Avenue, San Diego, California
92103

Full name of fourth inventor: Charles David Anderson

Inventor's signature Charles David Anderson


Date Oct. 4, 1993

Residence: Lebanon, New Jersey

Citizenship: United States of America

Post Office Address: 27 Potterstown Road, Lebanon, New Jersey
08833

Full name of fifth inventor: Jeffry G. Weers

Inventor's signature 

Date September 28, 1993

Residence: San Diego, California

Citizenship: United States of America

Post Office Address: 12191 Salix Way, San Diego, California 92129

Send Correspondence To:
KNOBBE, MARTENS, OLSON & BEAR
620 Newport Center Drive
Sixteenth Floor
Newport Beach, CA 92660-8016

Direct Telephone Calls To:
Ned A. Israelsen
(619) 235-8550

CAH-3766:lw
082693

67840 U.S. PROT
08/841847
05/05/97

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant	:	Schutt et al.)	Group Art Unit: 1209
Appl. No.	:	Unknown)	
Filed	:	Herewith)	
For	:	STABLE, GAS-FILLED MICROBUBBLE DISPERSIONS)	
Examiner	:	M. Cebulak)	

ASSOCIATE POWER OF ATTORNEY

Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

The following named person is hereby appointed an associate attorney to prosecute the above-identified application and take all actions respecting the same:

Christopher A. Dayton, Reg. No. 35,114
ALLIANCE PHARMACEUTICAL CORP.
3040 Science Park Road
San Diego, CA 92121

Please continue to send all correspondence to:

KNOBBE, MARTENS, OLSON & BEAR, LLP
620 Newport Center Drive
Sixteenth Floor
Newport Beach, CA 92660
(619) 235-8550

Respectfully submitted,

KNOBBE, MARTENS, OLSON & BEAR, LLP

Dated: 5-5-97

By: 

Ned A. Israelsen
Registration No. 29,655
Attorney of Record
620 Newport Center Drive
Sixteenth Floor
Newport Beach, CA 92660
(619) 235-8550

COPY

ALLIA.062A

PATENT

POWER OF ATTORNEY BY ASSIGNEE
AND
EXCLUSION OF INVENTOR UNDER 37 C.F.R. § 3.71

To the Commissioner of Patents and Trademarks:

The undersigned is empowered to act on behalf of the assignee indicated below (the "Assignee"). The original Assignment of the attached application for Letters Patent for the invention in STABILIZED MICROBUBBLE COMPOSITIONS, Serial No. 08/099,951, filed July 30, 1993, from the inventors to the Assignee has been submitted to the Assignment Branch for recordation. A true copy of this Assignment is attached hereto. I have reviewed the attached Assignment and hereby certify that to the best of the Assignee's knowledge and belief, the Assignee is the owner of the entire interest and title in the application for Letters Patent for the invention referred to above.

I declare that all statements made herein of my own knowledge are true, and that all statements made upon information and belief are believed to be true, and further, that these statements were made with the knowledge that willful, false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. § 1001, and that willful, false statements may jeopardize the validity of the application or any patent issuing thereon.

The Assignee hereby appoints Louis J. Knobbe, Registration No. 18,780; Don W. Martens, Registration No. 21,107; Gordon H. Olson, Registration No. 20,319; James B. Bear, Registration No. 25,221; Darrell L. Olson, Registration No. 28,247; William B. Bunker, Registration No. 29,365; William H. Nieman, Registration No. 30,201; John C. Lambertsen, Registration No. 29,400; Lowell Anderson, Registration No. 30,990; Arthur S. Rose, Registration No. 28,038; James F. Lesniak, Registration No. 25,240; Ned A. Israelsen, Registration No. 29,655; Drew S. Hamilton, Registration No. 29,801; Jerry T. Sewell, Registration No. 31,567; John B. Sganga, Jr., Registration No. 31,302; Edward A. Schlatter, Registration No. 32,297; Gerard von Hoffmann, Registration No.

33,043; William C. Rooklidge, Registration No. 31,791; Joseph R. Re, Registration No. 31,291; John M. Carson, Registration No. 34,303; Andrew H. Simpson, Registration No. 31,469; Daniel E. Altman, Registration No. 34,115; Anita M. Kirkpatrick, Registration No. 32,617; Vito A. Canuso, Registration No. 35,471; William H. Shreve, Registration No. 35,678; Stephen C. Jensen, Registration No. 35,556; Michael Fedrick, Registration No. 36,799; James F. Sweeney, Registration No. 32,445, Nancy Ways Vensko, Registration No. 36,298; Jonathan A. Barney, Registration No. 34,292; Myra H. McCormack, Registration No. 36,602; Renee E. Rogers, Registration No. 36,657; Guy L. Cumberbatch, Registration No. 36,114; Michael L. Fuller, Registration No. 36,516; and George T. Parsons, Registration No. 34,690, Knobbe, Martens, Olson & Bear, 620 Newport Center Drive, Sixteenth Floor, Newport Beach, California 92660, Telephone (619) 235-8550, as its attorneys to prosecute this application and to transact all business in the Patent Office connected therewith, said appointment to be to the exclusion of the inventor(s) and his attorney(s) in accordance with the provisions of 37 C.F.R. § 3.71.

Please direct all communications relative to said application to the following correspondence address:

KNOBBE, MARTENS, OLSON & BEAR
620 Newport Center Drive
Sixteenth Floor
Newport Beach, CA 92660

Telephone: (619) 235-8550

Assignee: ALLIANCE PHARMACEUTICAL CORP.

By : 
Theodore Roth

Title : Executive Vice President

Address : 3040 Science Park Road
San Diego, California 92121

Dated: October 28, 1993

COPY

Applicant or Patentee: Schutt et al.
Serial or Patent No.: 08/099,951
For: STABILIZED MICROBUBBLE COMPOSITIONS

Attorney's Docket No.: ALLIA.062A
Filed or Issued: July 30, 1993

VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS
(37 CFR 1.9(f) AND 1.27(c) - SMALL BUSINESS CONCERN)

I hereby declare that I am

- the owner of the small business concern identified below:
 an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF CONCERN: ALLIANCE PHARMACEUTICAL CORP.

ADDRESS OF CONCERN 3040 Science Park Road, San Diego, California 92121

I hereby declare that the above identified small business concern qualifies as a small business concern as defined in 13 CFR 121.3-18, and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees under section 41(a) and (b) of Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both. Furthermore, the concern has not assigned, granted, conveyed or licensed, and is under no obligation to assign, grant, convey or license any rights to the invention to any entity who would not be classified as a small entity.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention, entitled STABILIZED MICROBUBBLE COMPOSITIONS by inventor(s) Ernest G. Schutt, David P. Evitts, Rene Alta Kinner, Charles David Anderson, and Jeffry G. Weers described in

- the specification filed herewith
 application serial no. 08/099,951, filed July 30, 1993
 patent no. , issued

If the rights held by the above identified small business concern are not exclusive, each individual, concern or organization having rights to the invention is listed below and no rights to the invention are held by any person, other than the inventor, who could not qualify as a small business concern under 37 CFR 1.9(d) or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

*NOTE:

Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27).

FULL NAME:

ADDRESS:

INDIVIDUAL

SMALL BUSINESS CONCERN

NONPROFIT ORGANIZATION

FULL NAME:

ADDRESS:

INDIVIDUAL

SMALL BUSINESS CONCERN

NONPROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b)).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF PERSON SIGNING: Theodore Roth

TITLE OF PERSON OTHER THAN OWNER: Executive Vice President

ADDRESS OF PERSON SIGNING: 3040 Science Park Road, San Diego, California 92121

SIGNATURE

DATE:

October 28, 1993